



# Centaurus Basic PDU IEC 320 C13x12, with Lighted CB Switch, with Input - IEC 320 C14 (Power Cord not included)



## Applicable Standards

UL 62368-1

EN IEC 62368-1

Certification / Approvals : c(TUV)us | CE

## Product Part Number

N51.IEC121500

## Product Description

This Centaurus Basic PDU provides reliable power distribution with 12 IEC 320 C13 outlets and a lighted circuit breaker switch for overload protection. Featuring an IEC 320 C14 input (power cord sold separately), this PDU is ideal for powering multiple devices in server racks, data centers, and network environments. Compact and efficient, it offers a simple yet effective solution for your power management needs. The PDU can be mounted vertically or horizontally on a rack and features a built-in circuit breaker to protect equipment from damage. It is TUV and CE certified, and compatible with detachable power cords for different plug types, such as NEMA and IEC. The PDU is designed for IT environments, complies with safety standards (EN IEC 62368-1, UL 62368-1).

## Product Features

- Compact 1U rack-mount design
- Front-facing C13 outlets and C14 inlet for flexible configurations
- Built-in overload protection to safeguard connected equipment
- Supports both horizontal and vertical mounting options
- Compatible with separate power cables featuring a variety of plug types
- Ideal for server cabinets, data centers, and network closets.



# Centaurus Basic PDU IEC 320 C13x12, with Lighted CB Switch, with Input - IEC 320 C14 (Power Cord not included)

## Material Specifications

Power Rating	125V/15A or 250V/10A
Outlet Type	IEC 320 C13 x 12 (Front)
Inlet Type	IEC 320 C14 (Front)
Circuit Breaker with Lighted Switch	Yes   15A
Current & Voltage Meter	Yes
AC Rating Volts	100-125Vac
AC Rating Amps	12Amp
AC Rating Frequency	50/60 Hz
Shell Color	Black

## Environmental Specifications

Operating Temperature Range	0°C to 40°C
Storage Temperature Range	0°C to 40°C

## Ordering Information

N51.IEC121500	Centaurus Basic PDU, IEC 320 C13 x 12 (Front 12; Rear 0) with Lighted Circuit Breaker Switch, with Input - IEC 320 C14 x 1 (Power Cord not included)
---------------	--

## Shipping Information

Item	Dimension
Product	Width : 480.7 mm Height : 44.0 mm Depth : 33.0 mm