



# Centaurus Metered PDU IEC 320 C13x10 & IEC 320 C19x2, with Lighted CB Switch and Meter (Current & Voltage), with Input - IEC 320 C20 (Power Cord not included)



## Applicable Standards

UL 62368-1

EN IEC 62368-1

Certification / Approvals : c(TUV)us | CE

## Product Part Number

N52.IEC122000M

## Product Description

This Centaurus Metered PDU features 10 IEC 320 C13 and 2 IEC 320 C19 outlets, ideal for powering servers, computers, and network equipment. Equipped with a lighted switch, built-in circuit breaker, and meter to monitor current and voltage, this PDU ensures reliable performance and protection. It includes an IEC 320 C20 input (power cord sold separately) and is designed for efficient power distribution in data centers and IT environments. The PDU can be mounted vertically or horizontally on a rack and features a built-in circuit breaker to protect equipment from damage. It is TUV and CE certified, and compatible with detachable power cords for different plug types, such as NEMA and IEC. The PDU is designed for IT environments, complies with safety standards (EN IEC 62368-1, UL 62368-1).

## Product Features

- Compact 1U rack-mount design
- Front-facing C13/C19 outlets and C20 inlet for flexible configurations
- Built-in overload protection to safeguard connected equipment
- Supports both horizontal and vertical mounting options
- Compatible with separate power cables featuring a variety of plug types
- Ideal for server cabinets, data centers, and network closets.



# Centaurus Metered PDU IEC 320 C13x10 & IEC 320 C19x2, with Lighted CB Switch and Meter (Current & Voltage), with Input - IEC 320 C20 (Power Cord not included)

## Material Specifications

Power Rating	125V/20A or 250V/16A
Outlet Type	IEC 320 C13 x 10 (Front) + IEC 320 C19 x 2 (Front)
Inlet Type	IEC 320 C20 (Front)
Circuit Breaker with Lighted Switch	Yes   20A
Current & Voltage Meter	Yes
AC Rating Volts	100-125Vac
AC Rating Amps	16Amp
AC Rating Frequency	50/60 Hz
Shell Color	Black

## Environmental Specifications

Operating Temperature Range	0°C to 40°C
Storage Temperature Range	0°C to 40°C

## Ordering Information

N52.IEC122000M	Centaurus Metered PDU, IEC 320 C13 x 10 + IEC 320 C19 x 2 (Front 12; Rear 0) with Lighted Circuit Breaker Switch and with Meter (Current & Voltage), with Input - IEC 320 C20 - TUV Certified (Power Cord not included)
----------------	---

## Shipping Information

Item	Dimension
Product	Width : 480.7 mm Height : 44.0 mm Depth : 33.0 mm