

Compact OTDR Launch Cable, SC/UPC to SC/UPC, SM G.657A1



Product Part Number

N723.OLCSCSC5A1yx

Product Description

This compact OTDR launch cable comes with single-mode G.657A1 fiber with SC/UPC to SC/UPC connectors for precise fiber optic testing. Designed for versatility, it features two splice positions for interchangeable connectors, built-in magnets for cabinet attachment, and a durable, portable housing.

Product Features

- Compact & Portable : Lightweight and easy to carry
- Connector Flexibility: Includes two splice positions, making connector types interchangeable (SC, LC, FC, ST, E2000).
- Magnetic Attachment : Built-in magnets allow secure fixation on cabinets for ease of use.
- High-Performance Fiber : Single Mode G.657A1 fiber ensures low-loss testing.
- Durable Design: Available in grey or black with robust housing to withstand field conditions.

Compact OTDR Launch Cable, SC/UPC to SC/UPC, SM G.657A1

Material Specifications

| Fiber Type | Single Mode G.657A1 | |
|---------------------------|---|----------|
| Fiber Length | 100m, 300mm, 500mm, 1000m, 1500m, 2000m | |
| Connector Type | SC/UPC to SC/UPC | |
| Connector Compatibility | SC, LC, FC, ST, E2000 | |
| Input & Output Diameter | 2.0mm | |
| Input & Output Length | 1.5m | |
| Splice Capacity | 2 splice positions | |
| Color of Housing | Grey or Black | |
| Connector Specification : | Max Insertion Loss | 0.15dB |
| | Return Loss | UPC 55dB |
| | Apex Offset | 0~30µm |
| | Fiber Height | ±50nm |
| | Radius of Curvature (UPC) | 7~25mm |

Environmental Specifications

| Operating Temperature Range | - 20°C to 60°C |
|-----------------------------|----------------|
| Storage Temperature Range | -30°C to 70°C |

Compact OTDR Launch Cable, SC/UPC to SC/UPC, SM G.657A1

Ordering Information

| N723.OLCSCSC5A11x | Compact OTDR Launch Cable, SC/UPC - SC/UPC, Single Mode G.657A1, 100m |
|--------------------|--|
| N723.0LCSCSC5A13x | Compact OTDR Launch Cable, SC/UPC - SC/UPC, Single Mode G.657A1, 300m |
| N723.OLCSCSC5A15x | Compact OTDR Launch Cable, SC/UPC - SC/UPC, Single Mode G.657A1, 500m |
| N723.0LCSCSC5A110x | Compact OTDR Launch Cable, SC/UPC - SC/UPC, Single Mode G.657A1, 1000m |
| N723.0LCSCSC5A115x | Compact OTDR Launch Cable, SC/UPC - SC/UPC, Single Mode G.657A1, 1500m |
| N723.0LCSCSC5A120x | Compact OTDR Launch Cable, SC/UPC - SC/UPC, Single Mode G.657A1, 2000m |

x = G (Grey Color Case); B (Black Color Case)

Shipping Information

| Item | Dimension | |
|---------|---|--|
| Product | Width: 100mm Depth : 100mm Height: 90mm | |