



DataVault Rack W600xD800, Glass Front & Solid Metal Rear Door



Applicable Standards

- **EIA/ECA-310-E** : Specifying requirements for 19-inch rack mounting. Ensures compatibility with standard IT and networking equipment.
- **IEC 60297** : Covering the mechanical structure of 19-inch equipment racks
- **RoHS (Restriction of Hazardous Substances)** : Ensures the rack materials are free from hazardous substances like lead, mercury, and cadmium, making it environmentally friendly.
- **CE Marking** : Indicates compliance with European health, safety, and environmental protection standards.

Product Part Number

N322.DVh68Axx

Product Description

The **DataVault Floor-Standing Rack** is a versatile and robust enclosure designed for IT and networking equipment. Featuring a tempered glass front door for easy monitoring and a solid metal rear door for enhanced security, this rack is ideal for data centers, server rooms, and commercial installations. With flexible mounting options and excellent cable management features, it ensures efficient and secure equipment organization.

Product Features

- **Front Door** : Single tempered glass door with Swing Handle Lock for visibility and security
- **Rear Door** : Single solid metal door with a O-lock for added protection.
- **Durable Design** : Sturdy steel construction with a powder-coated finish for long-lasting durability.
- **Cable Management** : Includes a bottom sliding cable entry plate and top cable entry points for efficient cabling.
- **Customizable** : Comes with 4 adjustable 19" mounting rails, marked with "U" spacing in both directions (top-to-bottom and bottom-to-top).
- **Side Panels** : Split side panels with O-locks for easy access and added security.
- **Mobility & Stability** : Comes with leveling feet; optional castors can be ordered separately.
- **Optional Side Brackets** : Can be installed with optional 19" side brackets for vertically mounting equipment.





DataVault Rack W600xD800, Glass Front & Solid Metal Rear Door

Material Specifications

Sizes Available	32U, 36U, 42U
Dimensions (W x D)	600mm x 800mm
Front Door	Single tempered glass door with Swing Handle lock
Rear Door	Single solid metal door with O-lock
Construction Material	1.2mm high-quality steel, powder-coated
Cable Entry	Top and bottom entry points, including a bottom sliding cable entry plate
Mounting Rails	4 Nos. of adjustable 19" mounting rails
Weight Capacity	Up to 800 kg
U Marking	Available in both directions (top-to-bottom and bottom-to-top)
Side Panels	Split side panels with O-locks
Ventilation	Optional fan units can be installed, top perforations already available for Airflow
Mobility Options	Comes with leveling feet; Optional castors should be ordered separately
Vertical Cable Managers	Not available. Should be ordered separately

Environmental Specifications

Operating Temperature Range	5°C to 45°C
Storage Temperature Range	-20°C to 60°C



Ordering Information

N322.DV3268Axx	DataVault 32U, Floor Standing Rack W600mm D800mm, Front : Single Glass Door, Rear : Single Solid Metal Door
N322.DV3668Axx	DataVault 36U, Floor Standing Rack W600mm D800mm, Front : Single Glass Door, Rear : Single Solid Metal Door
N322.DV4268Axx	DataVault 42U, Floor Standing Rack W600mm D800mm, Front : Single Glass Door, Rear : Single Solid Metal Door

xx = Color Code : LG (Light Grey RAL 7035), BK (Black RAL 9005)

Shipping Information

Item	Dimension
Product	Width : 600 mm Height : 1608mm (32U) 1786mm (36U) 2053 mm (42U) Depth : 800mm