



Centaurus Basic 0U PDU 24 x 20A NEMA 5-20R Receptacle, with 20A CB and 6ft Power Cord with NEMA 5-20P Plug



Applicable Standards

UL Rating : 60950-1

Product Part Number

N51.242001A06

Product Description

The **Centaurus Basic 0U PDU** is a reliable and space-efficient power distribution unit designed for high-power IT environments, data centers, and enterprise network installations. Featuring **24 NEMA 5-20R receptacles**, a **20A circuit breaker** for overload protection, and a **6ft power cord** with a **NEMA 5-20P plug**, this PDU delivers stable and efficient power distribution. The **0U vertical design** helps maximize rack space, while the integrated **red LED power indicator** provides quick visual confirmation of power status.

Product Features

- 0U Vertical Design : Saves valuable rack space for optimized equipment layout.
- 24 x NEMA 5-20R Outlets : Supports high-power devices with 20A-rated receptacles.
- 20A Circuit Breaker : Provides enhanced protection against overloads.
- Red LED Power Indicator : Provides clear power status visibility.
- Durable Metal Housing : Enhances durability for long-term reliability.
- Easy Installation : Compatible with standard IT racks and enclosures.





Centaurus Basic 0U PDU 24 x 20A NEMA 5-20R Receptacle, with 20A CB and 6ft Power Cord with NEMA 5-20P Plug

Material Specifications

Power Rating	20A (Derated to 16A), 120VAC
Mounting	0U (Vertical)
AC Outlet Receptacle	24 x NEMA 5-20R
Max. Output Per Outlet	16Amp
Circuit Breaker	Yes 20A
Surge Protection	N/A
Power Indicator : Red LED	Yes
Power Cord	SJT, 12AWG x 3C 6ft
Plug Type	NEMA 5-20P
AC Rating Volts	120Vac
AC Rating Amps	20Amp
AC Rating Watts	2400W
AC Rating Frequency	50/60 Hz
Shell Color	Black

Environmental Specifications

Operating Temperature Range	0°C to 40°C
Storage Temperature Range	0°C to 40°C

Ordering Information

N51.242001A06	Centaurus Basic 0U (Vertical) PDU, 24 x 20A NEMA 5-20R Receptacle, with Circuit Breaker (20Amp) and Power Cord SJT 12AWG/3C, 6ft with NEMA 5-20P Plug
---------------	---





Centaurus Basic OU PDU 24 x 20A NEMA 5-20R Receptacle, with 20A CB and 6ft Power Cord with NEMA 5-20P Plug

Shipping Information

Item	Dimension
Product	Width : 38 mm Height : 1524 mm Depth : 38 mm

