



FotonShield MD MPO-LC Cassette, 24F with 3Nos. of 8F MPO (Male) Low Loss - 8 x LC/APC, SM OS2



Applicable Standards

- IEC 61754-20 : Fiber Optic Connector Interfaces – Part 20: LC Connectors
- IEC 61754-7 : Fiber Optic Connector Interfaces – MPO Connectors
- ISO/IEC 11801 : Generic Cabling for Customer Premises
- IEC 61300-3-35 (End-Face Cleanliness)
- RoHS and REACH

Product Part Number

N176.MPO8x3LCA5A

Product Description

The **FotonShield MD MPO-LC Cassette** is a high-density fiber breakout solution designed for seamless MPO-to-LC conversion in **single-mode OS2** fiber networks. Featuring **three 8F MPO (Male) low-loss connectors** at the rear and **12 LC/APC duplex adapters** at the front, this cassette ensures efficient 24-fiber management in high-speed 40G, 100G, and beyond network environments. Built with a secure locking mechanism and a fully enclosed protective housing, it offers optimized performance, quick deployment, and reduced insertion loss, making it an ideal solution for data centers, enterprise networks, and telecom infrastructures.

Product Features

- Triple 8F MPO (Male) Low-Loss Connectivity : Supports three 8-fiber MPO trunk cables, providing high-speed optical networking.
- Three 8 x LC/APC Ports for Breakout : Provides a structured, high-density fiber termination solution with low insertion loss.
- Low-Loss Performance : Utilizes premium-grade ferrules to ensure minimal insertion loss, supporting long-distance OS2 networks.
- Polarity A (Straight-Through Configuration) : Ensures proper alignment in structured cabling environments.
- UL-94 V0 Flame-Retardant ABS + PC Housing : High durability, impact resistance, and enhanced fire safety.
- Plug-and-Play Modular Design : Enables fast and easy deployment in high-density rack-mount environments.
- Reliable Locking Mechanism : Push-Down to Release & Pull to Remove system for secure and effortless cassette mounting.





FotonShield MD MPO-LC Cassette, 24F with 3Nos. of 8F MPO (Male) Low Loss - 8 x LC/APC, SM OS2

Material Specifications

Type	MD MPO-LC Cassette (with 3 Nos. of 8F MPO Low Loss - 8 x LC/APC)
Fiber Type	Single Mode OS2
LC Connector	Insertion Loss : ≤ 0.25 dB, Return Loss : APC ≥ 65 dB
MPO (Elite) Connector	Insertion Loss : ≤ 0.35 dB, Return Loss : APC ≥ 65 dB
Adapter Type	Duplex LC/APC
Polarity	Type A (Straight-Through)
Housing Material	ABS + PC (UL-94 V0 Flame-Retardant)
Application	Data Centers, Enterprise Networks, High-Density Fiber Distribution, 40G/100G/400G Deployments

Environmental Specifications

Operating Temperature Range	- 20°C to 70°C
Storage Temperature Range	- 20°C to 70°C

Ordering Information

N176.MPO8x3LCA5A	FotonShield MD MPO-LC Cassette, 24F with 3Nos. of 8F MPO (Male) Low Loss - 8 x LC/APC, SM OS2
------------------	---

