



# PoE Splitter, 100Mbps, 12V Output



## Compliance & Standards

- IEEE 802.3af (PoE)
- RoHS Compliant
- FCC Part 15, Class B
- EN 55022 (Emissions), EN 55024 (Immunity), VCCI

## Product Part Number

N89.PS100-12V

## Product Description

Designed for seamless integration with legacy 12V-powered network devices, this **100Mbps PoE splitter** efficiently extracts power from an IEEE 802.3af-compliant PoE line and converts it to a regulated **12V DC output** (up to 13W). It allows the deployment of non-PoE equipment—such as IP cameras or access control systems—without the need for local power adapters.

Equipped with a built-in **DC/DC converter**, surge protection, and easy plug-and-play functionality, this isolated splitter is ideal for long-distance, low-voltage applications up to 100 meters.

## Product Features

- IEEE 802.3af compliant for reliable PoE operation
- Supports 10/100Mbps Ethernet networks
- Built-in DC/DC converter eliminates the need for external power adapters
- LED indicators for PoE and Link/Activity status
- Plug-and-play installation – no software or configuration required
- Isolated output design for enhanced equipment protection
- Integrated 1.5kV surge protection
- EMI compliance with FCC, CE Class B
- Supports PoE transmission distance up to 100 meters

## Applications

- IP Cameras (fixed and dome)
- CCTV Surveillance Systems
- Access Control Panels
- Infrared (IR) Illuminators
- DVRs & Video Processing Units





### Material Specifications

Data Rates	10/100Mbps
Input Power Voltage	44 – 57V DC
Input Power Consumption	15.4W
Output Power	12V DC / 1A (Max 13W)
Pin Assignment & Polarity	1/2(+), 3/6(-); 4/5(+), 7/8(-)
LED Indicators	PoE Power, Link/Activity
Connectors	Shielded RJ45, EIA/TIA 568A & 568B compliant
Surge Protection	RJ45 Port : 1.5kV
EMI / EMC Compliance	FCC Part 15 Class B, EN 55022, EN 55024, VCCI
Regulatory Compliance	IEEE 802.3af, CE, FCC, RoHS
Reliability	MTBF : 100,000 hours @ 25°C
Dimensions	150mm × 65mm × 38mm
Weight	560gm

### Environmental Specifications

Temperature range	Storage & shipping	-20°C to +70°C
	Operation	-10°C to +45°C

### Ordering Information

N89.PS100-12V	PoE Splitter – 100Mbps, 12V Output
---------------	------------------------------------

### Note

Please read this manual thoroughly before connecting your device. **Incorrect connections may result in fire, electric shock, or equipment damage.**



NORTHERN  
LINK

## PoE Splitter, 100Mbps, 12V Output

### Shipping Information

Item	Dimension	Nominal Net Weight
Product	Length : 150mm Width : 65mm Height : 38mm	Weight : 560gm

